

LED DEĞER TABLOSU / LED TABLE VALUE



		TEK RENK / ONE COLOR								
		LED SAYISI / LED PCS								
		24 LEDLİ / 24 LED			48 LEDLİ / 48 LED			72 LEDLİ / 72 LED		
ÜRÜN PRODUCT	RENK COLOR	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)
İŞIKLI KİLİTLİ PARKE	AMBER	1,92	0,16	88,80	3,84	0,32	177,60	5,76	0,48	266,40
İŞIKLI KİLİTLİ PARKE	BEYAZ	1,92	0,16	52,80	3,84	0,32	105,60	5,76	0,48	158,40
İŞIKLI KİLİTLİ PARKE	KIRMIZI	1,92	0,16	52,80	3,84	0,32	105,60	5,76	0,48	158,40
İŞIKLI KİLİTLİ PARKE	MAVI	1,92	0,16	24,00	3,84	0,32	48,00	5,76	0,48	72,00
İŞIKLI KİLİTLİ PARKE	YEŞİL	1,92	0,16	88,80	3,84	0,32	177,60	5,76	0,48	266,40
İŞIKLI KİLİTLİ PARKE	G.İŞİĞİ	1,92	0,16	40,80	3,84	0,32	81,60	5,76	0,48	122,40
İŞIKLI KİLİTLİ PARKE	LILA	-	-	-	3,84	0,32	76,80	-	-	-
İŞIKLI KİLİTLİ PARKE	TURKUAZ	-	-	-	3,84	0,32	112,80	-	-	-

		ÇİFT RENK AYNI ANDA								
		LED SAYISI / LED PCS								
		24 LEDLİ / 24 LED			48 LEDLİ / 48 LED			72 LEDLİ / 72 LED		
ÜRÜN PRODUCT	RENK COLOR	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)
İŞIKLI KİLİTLİ PARKE	KIRMIZI-AMBER	1,92	0,16	26,40-44,40	3,84	0,32	52,80-88,80	5,76	0,48	79,20-133,20
İŞIKLI KİLİTLİ PARKE	KIRMIZI-BEYAZ	1,92	0,16	26,40-26,40	3,84	0,32	52,80-52,80	5,76	0,48	79,20-79,20
İŞIKLI KİLİTLİ PARKE	KIRMIZI-MAVI	1,92	0,16	26,40-12,00	3,84	0,32	52,80-24,00	5,76	0,48	79,20-72,00
İŞIKLI KİLİTLİ PARKE	KIRMIZI-YEŞİL	1,92	0,16	26,40-44,40	3,84	0,32	52,80-88,80	5,76	0,48	79,20-133,20
İŞIKLI KİLİTLİ PARKE	MAVI-AMBER	1,92	0,16	12,00-44,40	3,84	0,32	24,00-88,80	5,76	0,48	36,00-133,20
İŞIKLI KİLİTLİ PARKE	MAVI-BEYAZ	1,92	0,16	12,00-26,40	3,84	0,32	24,00-52,80	5,76	0,48	36,00-79,20
İŞIKLI KİLİTLİ PARKE	MAVI-YEŞİL	1,92	0,16	12,00-44,40	3,84	0,32	24,00-88,80	5,76	0,48	36,00-133,20
İŞIKLI KİLİTLİ PARKE	YEŞİL-AMBER	1,92	0,16	44,40-44,40	3,84	0,32	88,80-88,80	5,76	0,48	133,20-133,20
İŞIKLI KİLİTLİ PARKE	YEŞİL-BEYAZ	1,92	0,16	44,40-20,40	3,84	0,32	88,80-52,80	5,76	0,48	133,20-79,20

		ÇİFT RENK AYRI AYRI								
		LED SAYISI / LED PCS								
		24 LEDLİ / 24 LED			48 LEDLİ / 48 LED			72 LEDLİ / 72 LED		
ÜRÜN PRODUCT	RENK COLOR	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)
İŞIKLI KİLİTLİ PARKE	AMBER+BEYAZ	1,92	0,16	88,80-52,80	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	AMBER+KIRMIZI	1,92	0,16	88,80-52,80	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	AMBER+MAVI	1,92	0,16	88,80-24,00	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	AMBER+YEŞİL	1,92	0,16	88,80-44,40	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	AMBER+G.İŞİĞİ	1,92	0,16	88,80-40,80	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	BEYAZ+KIRMIZI	1,92	0,16	52,80-52,80	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	BEYAZ+MAVI	1,92	0,16	52,80-24,00	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	BEYAZ+YEŞİL	1,92	0,16	52,80-44,40	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	BEYAZ+G.İŞİĞİ	1,92	0,16	52,80-40,80	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	KIRMIZI+MAVI	1,92	0,16	52,80-24,00	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	KIRMIZI+YEŞİL	1,92	0,16	52,80-44,40	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	KIRMIZI+G.İŞİĞİ	1,92	0,16	52,80-40,80	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	MAVI+YEŞİL	1,92	0,16	24,00-44,40	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	MAVI+G.İŞİĞİ	1,92	0,16	24,00-40,80	-	-	-	-	-	-
İŞIKLI KİLİTLİ PARKE	YEŞİL+G.İŞİĞİ	1,92	0,16	44,40-40,80	-	-	-	-	-	-

		RGB								
		LED SAYISI / LED PCS								
		24 LEDLİ / 24 LED			48 LEDLİ / 48 LED			72 LEDLİ / 72 LED		
ÜRÜN PRODUCT	RENK COLOR	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)	GÜÇ TÜKETİMİ (W) POWER (W)	AKIM (A) CURRENT (A)	IŞIK AKISI (Lm) LIGHT INTENSITY (Lm)
İŞIKLI KİLİTLİ PARKE	RGB	-	-	-	-	-	-	5,76	0,48	52,80-88,80-24,00

TEKNOFORS

TEKNOLOJİ ve LED AYDINLATMA

Fatih Mh.Karatay San.Ömerli Sk.No:9/A 42300 Selçuklu/KONYA
 Telefon :0-332-222 00 11 Fax:0-332-222 00 11
 www.teknofors.com bilgi@teknofors.com
 info@teknofors.com